

Project:

Fixture Type:

Location:

Quadrant LED

Ceiling Mounted • Damp Location Listed PROGRESS LED

Contact:

Description:

Quadrant LED Collection 4-Light Matte Black Frosted Glass Modern Flush Mount Ceiling Light

Specifications:

- · Frosted Acrylic Cylindrical
- · Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 7.0625 in W., 7.0625 in ht., 1.375 in depth
- · Mounting backplate for outlet box included
- 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

Performance:

Number of Modules	4
Input Power	25 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,261/53 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2019

P350209-031-30



Dimensions:

Length: 20-1/16 in Diameter: 20-1/16 in Height: 4 in

Frosted Acrylic Cylindrical

Width: 1-1/4 in Height: 4-3/4 in



Quadrant LED

Ceiling Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

P350209-031-30

P350209-031-30 is designed to be compatible with many ELV controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.